

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS #: 082122 TALUSIA UNIVERSAL 100

Date of the previous version: 2018-02-07 Revision Date: 2018-02-14 Version 3.04

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE

COMPANY/UNDERTAKING

1.1. Product identifier

Product name TALUSIA UNIVERSAL 100

Number CCW Substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Motor oil.

1.3. Details of the supplier of the safety data sheet

Supplier TOTAL LUBRIFIANTS

562 Avenue du Parc de L'ile 92029 Nanterre Cedex

FRANCE

Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

For further information, please contact:

Contact Point HSE

E-mail Address rm.msds-lubs@total.com

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670

France - ORFILA (INRS) Tél: +33 (0)1 45 42 59 59

In France - Poison centers: ANGERS: 02 41 48 21 21 BORDEAUX: 05 56 96 40 80 LILLE: 08 00 59 59 59 LYON: 04 72 11 69 11 MARSEILLE: 04 91 75 25 25 NANCY: 03 83 22 50 50

PARIS: 01 40 05 48 48 STRASBOURG: 03 88 37 37 37 TOULOUSE: 05 61 77 74 47

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008



SDS #: 082122

TALUSIA UNIVERSAL 100

Revision Date: 2018-02-14 Version 3.04

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

Classification

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008

2.2. Label elements

Labelled according to

REGULATION (EC) No 1272/2008

Signal word

None

Hazard Statements

None

Precautionary Statements

None

Supplemental Hazard Statements

EUH210 - Safety data sheet available on request

2.3. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental propertiesThe product may form an oil film on the water surface that may stop the oxygen exchange.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture

Chemical nature
Hazardous ingredients

Mineral oil of petroleum origin.

nazardous ingredients	=0.11		2121	T 184 1 1 4 04	01 10 11 (0 1000)
Chemical Name	EC-No	REACH registration	CAS-No	Weight %	Classification (Reg. 1272/2008)
		No			
Distillates (petroleum), hydrotreated heavy paraffinic	265-157-1***	01-2119484627-25	64742-54-7	10-<20	Asp. Tox. 1 (H304)
Phenol, dodecyl-, branched	310-154-3***	01-2119513207-49-0 002	121158-58-5	0.1-<0.3	Skin Corr. 1C (H314) Eye Dam. 1 (H318) Repr. 1B (H360F) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M factor acute = 10 M factor chronic =10

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

For the full text of the H-Statements mentioned in this Section, see Section 16.



TALUSIA UNIVERSAL 100

Revision Date: 2018-02-14 Version 3.04

Section 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while

rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before reuse. Remove contaminated

clothing and shoes. Wash off with soap and water.

Inhalation Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, give artificial respiration. Inhalation of high concentrations of vapor or aerosols

may cause irritation of the upper respiratory tract.

Ingestion Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician or Poison Control Center immediately. If swallowed,

do not induce vomiting - seek medical advice.

Protection of First-aiders First aider needs to protect himself. See Section 8 for more detail. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

respiratory medical device. Use personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact Not classified based on available data.

Skin contact Not classified based on available data.

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media Carbon dioxide (CO 2). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing MediaDo not use a solid water stream as it may scatter and spread fire.



Revision Date: 2018-02-14 Version 3.04

5.2. Special hazards arising from the substance or mixture

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may

be highly dangerous if inhaled in confined spaces or at high concentration.

5.3. Advice for fire-fighters

Special protective equipment for

fire-fighters

Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing

water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways,

sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained. Try to prevent the material from entering drains or water

courses. See Section 12 for additional Ecological Information.***

6.3. Methods and material for containment and cleaning up

Methods for containment Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or

similar non-combustible materials.

Methods for cleaning upDam up. Soak up with inert absorbent material. Keep in suitable, closed containers for

disposal. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according

to local / national regulations (see section 13).

6.4. Reference to other sections

Personal Protective Equipment See Section 8 for more detail.

Waste treatment See section 13.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling



Revision Date: 2018-02-14 Version 3.04

Advice on safe handling

For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. When using, do not eat, drink or smoke.

Prevention of fire and explosion

Take precautionary measures against static discharges.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Wash hands with water as a precaution. Avoid breathing vapors, mist or gas. Do not wash off with:. Fuel. Solvent. Abrasive. Avoid extended and repeated contact with the skin as this may cause skin conditions, which may also be aggravated by minor injuries or by contact with soiled clothing. Avoid prolonged and repeated contact with the skin, especially with used or waste product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture. Protect from frost, heat and sunlight. Store in original container. Keep in properly labeled containers.

Materials to Avoid

Strong oxidizing agents.

7.3. Specific end uses

Specific use(s)

Please refer to Technical Data Sheet for further information.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m^3 , NIOSH (REL) TWA 5 mg/m^3 , STEL 10 mg/m^3 , ACGIH

(TLV) TWA 5 mg/m³ (highly refined)

Legend See section 16

Derived No Effect Level (DNEL)

DNEL Worker (Industrial/Professional)

DNLL Worker (Industrial/Froiessional)					
Chemical Name	Short term, systemic	Short term, local effects	Long term, systemic	Long term, local effects	
	effects		effects		
Distillates (petroleum),				5.4 mg/m ³ /8h (aerosol -	



Revision Date: 2018-02-14 Version 3.04

hydrotreated heavy paraffinic 64742-54-7			inhalation)
Phenol, dodecyl-, branched 121158-58-5	44.18 mg/m³ Inhalation 166 mg/kg Dermal	1.7621 mg/m³ Inhalation 0.25 mg/kg Dermal	

DNEL Consumer

Chemical Name	Short term, systemic	Short term, local effects	Long term, systemic	Long term, local effects
	effects		effects	
Distillates (petroleum),				1.2 mg/m ³ /24h (aerosol -
hydrotreated heavy				inhalation)
paraffinic				·
64742-54-7				
Phenol, dodecyl-,	13.26 mg/m3 Inhalation		0.79 mg/m3 Inhalation	
branched	50 mg/kg Dermal		0.075 mg/kg Dermal	
121158-58-5	1.26 mg/kg Oral		0.075 mg/kg Oral	

Predicted No Effect Concentration (PNEC)

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
Phenol, dodecyl-,	0.000074 mg/l fw	0.226 mg/kg dw	0.118 mg/kg dw		100 mg/l	4 mg/kg food
branched	0.0000074 mg/l	fw			_	
121158-58-5	mw	0.0266 mg/kg dw				
	0.00037 mg/l or	mw				

8.2. Exposure controls

Occupational Exposure Controls

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.***

Personal Protective Equipment

General Information Protective engineering solutions should be implemented and in use before personal

protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is

suggested that you contact the relevant PPE suppliers.**

Respiratory protectionNone under normal use conditions. When workers are facing concentrations above the

exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P1. Warning! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's

instructions and the regulations governing their choices and uses.

Eye Protection If splashes are likely to occur, wear:. Safety glasses with side-shields. EN 166.

Skin and body protectionWear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type

4/6. Do not wear rings, watches or anything similar which can retain the product and may give rise to skin conditions. Extended and repeated contacts with skin can cause skin ailments which may be aggravated by minor injuries or contact with soiled clothing.



> **Revision Date: 2018-02-14** Version 3.04

Hand Protection

Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

Environmental exposure controls

Boiling point/boiling range

General Information The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance limpid

Color No information available

liquid Physical State @20°C Odor

Characteristic **Odor Threshold**

No information available

Values Method Property Remarks

Not applicable No information available Melting point/range

Flash point 220 °C Cleveland Open Cup (COC)

No information available

428 °F Cleveland Open Cup (COC)

Evaporation rate No information available

Flammability Limits in Air

No information available upper

Lower No information available No information available **Vapor Pressure** Vapor density No information available

@ 15 °C ISO 2049 Relative density 0.940 - 0.960 @ 15 °C 940 - 960 kg/m³ **Density** ISO 2049

Insoluble Water solubility Solubility in other solvents No information available

loaPow No information available Autoignition temperature No information available No information available **Decomposition temperature**

ISO 3104 Viscosity, kinematic 199.4 mm2/s @ 40 °C



Revision Date: 2018-02-14 Version 3.04

Explosive propertiesOxidizing Properties
Not explosive
Not applicable

Possibility of hazardous reactions None under normal processing

9.2. Other information

Freezing Point No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

General Information None under normal processing.***

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions No dangerous reaction known under conditions of normal use.***

10.4. Conditions to avoid

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat

and sparks.**

10.5. Incompatible materials

Materials to Avoid Strong oxidizing agents.***

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Hydrogen fluoride. Sodium oxides. Phosphorous oxides. Hydrogen chloride. Nitrogen oxides (NOx). Mercaptans. Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen

sulphide H2S. Zinc oxides. Silicon dioxide.**

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact . Not classified based on available data.

Eye contact . Not classified based on available data.



Revision Date: 2018-02-14 Version 3.04

Inhalation

. Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.

Ingestion

. Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

ATEmix (inhalation-dust/mist)

31.70 mg/l

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy	LD50 > 5000 mg/kg bw (rat -	LD50 > 5000 mg/kg bw (rabbit -	LC50 (4h) > 5 mg/l (aerosol) (rat -
paraffinic	OECD 420)	OECD 402)	OECD 403)
Phenol, dodecyl-, branched	LD50 2200 mg/kg (Rat)	LD50 15000 mg/kg (Rabbit - male	
·		- OECD402)	

Sensitization

Sensitization Not classified based on available data.

Specific effects

Carcinogenicity Not classified based on available data. During use in engines, contamination of oil with low

levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil

is thoroughly removed by washing with soap and water.

Mutagenicity

Germ Cell Mutagenicity Not cl

Not classified based on available data. Not classified based on available data.

Reproductive toxicity

Not classified based on available data. Contains toxic substance(s) listed as toxic to

reproduction.

Chemical Name	European Union
Phenol, dodecyl-, branched	Repr. 1B (H360F)
121158-58-5	

Repeated Dose Toxicity

Target Organ Effects (STOT)

Specific target organ systemic toxicity (single exposure)

Not classified based on available data.

Specific target organ systemic toxicity (repeated exposure)

Not classified based on available data.

Aspiration toxicity Not classified based on available data.

Other information

Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated

exposures (contact with contaminated clothing).

Section 12: ECOLOGICAL INFORMATION



SDS #: 082122

TALUSIA UNIVERSAL 100

Revision Date: 2018-02-14 Version 3.04

12.1. Toxicity

Not classified based on available data. This product contains one or more components that have a branched alkylphenol impurity which is very toxic to aquatic life (disclosed in section 3). Components containing the impurity have been tested and are not toxic to aquatic life. Therefore, the data in Section 3 for the alkylphenol impurity should not be used to classify the product for aquatic toxicity.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and	Toxicity to fish	Toxicity to
		other aquatic invertebrates		microorganisms
Distillates (petroleum),	EL50 (48h) > 100 mg/l	EL50 (48h) > 10000 mg/l	LL50 (96h) > 100 mg/l	
hydrotreated heavy	(Pseudokirchnerella	(Daphnia magna - OECD	(Oncorhynchus mykiss -	
paraffinic	subcapitata - OECD 201)	202)	OECD 203)	
64742-54-7	,	,	,	
Phenol, dodecyl-, branched	EbC50 (72h) 0.15 mg/l	EC50 (48h) 0.037 mg/l	EL50 (96h) 40 mg/l	
121158-58-5	(Scenedesmus subspicatus -	(Daphnia magna -OECD	(Pimephales promelas -	
	OECD 201)	202)	OECD 203)	

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Phenol, dodecyl-, branched 121158-58-5		NOEC (21d) 0.004 mg/l (Daphnia magna - semi static - OECD211)		

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information

No information available.



SDS #: 082122

TALUSIA UNIVERSAL 100

Revision Date: 2018-02-14 Version 3.04

logPow No information available

Component Information

component information :					
Chemical Name	log Pow				
Distillates (petroleum), hydrotreated heavy paraffinic - 64742-54-7	-				
Phenol, dodecyl-, branched - 121158-58-5	7.14				

12.4. Mobility in soil

Soil Given its physical and chemical characteristics, the product generally shows low soil

mobility.

Air Loss by evaporation is limited.

Water The product is insoluble and floats on water.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

General Information No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products

Should not be released into the environment. Do not empty into drains. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.***

EWC Waste Disposal No.

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions:. 13 02 05.

Other information

Refer to section 8 for safety and protective measures for disposal personnel. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORT INFORMATION

ADR/RID

Not regulated



Revision Date: 2018-02-14 Version 3.04

IMDG/IMO Not regulated

ICAO/IATA Not regulated

ADN Not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture_

European Union

Further information

No information available

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H360F - May damage fertility

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development



Revision Date: 2018-02-14 **Version** 3.04

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight fw = fresh water mw = marine water or = occasional release

Legend Section 8

TWA: Time Weight Average STEL: Short Time Exposure Limit PEL: Permissible exposure limit REL: Recommended exposure limit

TLV: Threshold Limit Values

+ Sensitizer * Skin designation

** Hazard Designation C: Carcinogen

M: Mutagen R: Toxic to reproduction

Revision Date: 2018-02-14

Revision Note *** Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet